



OLYMPIC 30SR		YAMAHA 300hp		PROPELLER	
Hull Type	Deep-V stepped	Engine	4 Stroke – V6	HS4	15"x 23"
Deadrise at transom	21.5 degrees	HP	300	Blades	4
Dry Weight	1600 Kg	Displacement	4.2L	Material	S. Steel
Length	9m	Weight	250-265 kg		
Beam	2.92m	Operating Range	5000 - 6000 rpm	MOUNTING HEIGHT	
Max power	2x40hp	Gear Ratio	1.75:1	Hole Position	1st
Fuel capacity	500lts			Jack Plate	No
Water capacity	150lts			A/V plate-keel	-- cm

www.olr.gr

www.yamahamarine.com

TEST CONDITIONS					
Sea State	2bf			Fuel	250ltrs
Wind speed	---kts			Crew Weight	190 Kg
Waves height	0.3-0.5m			Equipment Weight	200 Kg

PERFORMANCE DATA						USEFUL REMARKS	
RPM	KNOTS	LPH	LPM	SLIP	RANGE*	On Plane	9 Knots@ 1700rpm
3000	27	46	1.7	17%	147nm	W.O.T.	6000rpm
3500	34	66	1.9	10%	132nm	Top Speed	59 Knots
4000	40	86	2.1	7.5%	119nm	Acceleration	0-30 Knots in 7sec
4500	45	108	2.4	7.5%	104nm	Time to plane	4 sec
5000	50	138	2.7	7.5%	93nm	Best Fuel Efficiency	1.7lpm @ 3000rpm
5500	55	170	3.1	7.5%	81nm	Optimum Range	147nm with 250lts of fuel @ 27kts
6000	59	202	3.4	9%	74nm		

*The range numbers correspond roughly to the quantity of fuel we had during our sea trial.